


**PRODUCT INFORMATION SHEET**



Replaceability of light sources and/or control gears without product permanent damage



**BASIC INFORMATION**

|                |                                       |
|----------------|---------------------------------------|
| Product name:  | <b>REGAL LED 12W CHROME NW</b>        |
| Ideus index:   | <b>00009</b>                          |
| EAN barcode:   | <b>5901477300097</b>                  |
| Colour :       | <b>Chrome</b>                         |
| Materials:     | <b>Stainless steel, acrylic glass</b> |
| Height:        | <b>45 mm</b>                          |
| Width:         | <b>520 mm</b>                         |
| Depth:         | <b>70 mm</b>                          |
| Box packaging: | <b>20 pcs</b>                         |

**PRODUCT PARAMETERS**

|   |                                       |
|---|---------------------------------------|
| Power supply:   | <b>230V 50Hz</b>                      |
| Power:  | <b>12 W</b>                           |
| Dedicated light source:   | <b>SMD LED, in set</b>                |
|   | <b>Non-replaceable light source</b>   |
|   | <b>Do not use with a mains dimmer</b> |
| Luminaire luminous flux:  | <b>780 lm</b>                         |
| Light colour:   | <b>Neutral white</b>                  |
| Luminous beam angle:  | <b>120°</b>                           |
| Shelf life L70B50 in h:   | <b>35 000 h</b>                       |
| Product offer the possibility of adjusting the illumination direction:              | <b>No</b>                             |
| Light source luminous flux for a reference colour temperature:                      | <b>1 330 lm</b>                       |
| Colour temperature:   | <b>4100 K</b>                         |
| Colour rendering index Ra:  | <b>84</b>                             |
| Electric shock protection class:  | <b>1</b>                              |
| Degree of protection provided against intrusion dust, accidental contact and water: | <b>IP20</b>                           |
|   | <b>For indoor use</b>                 |
| Displacement factor (DF, cos φ1):   | <b>0.855</b>                          |
| CE  | <b>Declaration of conformity</b>      |