


# PRODUCT INFORMATION SHEET



Replaceability of light sources and/or control gears without product permanent damage



## BASIC INFORMATION

|                |                             |
|----------------|-----------------------------|
| Product name:  | <b>RINGE LED 16W CCT</b>    |
| Ideus index:   | <b>03282</b>                |
| EAN barcode:   | <b>5901477332821</b>        |
| Colour :       | <b>White</b>                |
| Materials:     | <b>Steel sheet, plastic</b> |
| Height:        | <b>70 mm</b>                |
| Width:         | <b>350 mm</b>               |
| Depth:         | <b>350 mm</b>               |
| Box packaging: | <b>10 pcs</b>               |

## REMARKS

**Three-stage color temperature control (WW, NW, CW)**

## PRODUCT PARAMETERS

|   |  |
|---|--|
| Power supply:   | <b>230V 50Hz</b>                           |
| Power:  | <b>16 W</b>                                |
| Dedicated light source:   | <b>SMD LED, in set</b>                     |
|   | <b>Non-replaceable light source</b>        |
|   | <b>Do not use with a mains dimmer</b>      |
| Luminaire luminous flux:  | <b>1 375 lm</b>                            |
| Light colour:   | <b>Warm white/neutral white/cold white</b> |
| Luminous beam angle:  | <b>160°</b>                                |
| Shelf life L70B50 in h:   | <b>35 000 h</b>                            |
| Product offer the possibility of adjusting the illumination direction:              | <b>No</b>                                  |
| Light source luminous flux for a reference colour temperature:                      | <b>1 940 lm</b>                            |
| Colour temperature:   | <b>3000K/4200K/6500K</b>                   |
| Colour rendering index Ra:  | <b>82</b>                                  |
| Electric shock protection class:  | <b>1</b>                                   |
| Degree of protection provided against intrusion dust, accidental contact and water: | <b>IP20</b>                                |
|   | <b>For indoor use</b>                      |
| Displacement factor (DF, cos φ1):   | <b>0.824</b>                               |
| CE  | <b>Declaration of conformity</b>           |