


# PRODUCT INFORMATION SHEET



Replaceability of light sources and/or control gears without product permanent damage



## BASIC INFORMATION

|                |                                    |
|----------------|------------------------------------|
| Product name:  | <b>ROXANA LED 13W CHROME NW</b>    |
| Ideus index:   | <b>03749</b>                       |
| EAN barcode:   | <b>5901477337499</b>               |
| Colour :       | <b>Chrome</b>                      |
| Materials:     | <b>Aluminium, polycarbonate PC</b> |
| Height:        | <b>39 mm</b>                       |
| Width:         | <b>600 mm</b>                      |
| Depth:         | <b>111 mm</b>                      |
| Box packaging: | <b>20 pcs</b>                      |

## REMARKS

**For instaling in increased-humidity locations, e.g. bathrooms**

## PRODUCT PARAMETERS

|                                                                                     |                                       |
|-------------------------------------------------------------------------------------|---------------------------------------|
| Power supply:                                                                       | <b>230V 50Hz</b>                      |
| Power:                                                                              | <b>13 W</b>                           |
| Dedicated light source:                                                             | <b>SMD LED, in set</b>                |
|                                                                                     | <b>Non-replaceable light source</b>   |
|                                                                                     | <b>Do not use with a mains dimmer</b> |
| Luminaire luminous flux:                                                            | <b>845 lm</b>                         |
| Light colour:                                                                       | <b>Neutral white</b>                  |
| Luminous beam angle:                                                                | <b>110°</b>                           |
| Shelf life L70B50 in h:                                                             | <b>35 000 h</b>                       |
| Product offer the possibility of adjusting the illumination direction:              | <b>No</b>                             |
| Light source luminous flux for a reference colour temperature:                      | <b>1 430 lm</b>                       |
| Colour temperature:                                                                 | <b>4100 K</b>                         |
| Colour rendering index Ra:                                                          | <b>82</b>                             |
| Electric shock protection class:                                                    | <b>2</b>                              |
| Degree of protection provided against intrusion dust, accidental contact and water: | <b>IP44</b>                           |
|                                                                                     | <b>For indoor use</b>                 |
| Displacement factor (DF, cos φ1):                                                   | <b>0.739</b>                          |
| CE                                                                                  | <b>Declaration of conformity</b>      |