



# PRODUCT INFORMATION SHEET



Replaceability of light sources and/or control gears without product permanent damage



## BASIC INFORMATION

|                |                         |
|----------------|-------------------------|
| Product name:  | <b>TRAPER LED 1W+3W</b> |
| Ideus index:   | <b>03932</b>            |
| EAN barcode:   | <b>5901477339325</b>    |
| Colour :       | <b>Red/black</b>        |
| Materials:     | <b>Plastic</b>          |
| Height:        | <b>73 mm</b>            |
| Width:         | <b>73 mm</b>            |
| Depth:         | <b>205 mm</b>           |
| Box packaging: | <b>60 pcs</b>           |

## REMARKS

- with rechargeable battery
- lighting time for one charge maximum 6 h
- charging time: optimal 12 h, max. 15 h

## PRODUCT PARAMETERS

|                                                                                     |                                     |
|-------------------------------------------------------------------------------------|-------------------------------------|
| Power supply:                                                                       | <b>230V 50Hz</b>                    |
| Power:                                                                              | <b>1 W + 3 W</b>                    |
| Dedicated light source:                                                             | <b>LED, in set</b>                  |
|                                                                                     | <b>Non-replaceable light source</b> |
| Luminaire luminous flux:                                                            | <b>210 lm</b>                       |
| Light colour:                                                                       | <b>Cold white</b>                   |
| Luminous beam angle:                                                                | <b>4°</b>                           |
| Shelf life L70B50 in h:                                                             | <b>35 000 h</b>                     |
|                                                                                     | <b>On/off switch</b>                |
| Product offer the possibility of adjusting the illumination direction:              | <b>No</b>                           |
| Light source luminous flux for a reference colour temperature:                      | <b>90 lm + 120 lm</b>               |
| Colour temperature:                                                                 | <b>6000 K</b>                       |
| Colour rendering index Ra:                                                          | <b>80</b>                           |
| Electric shock protection class:                                                    | <b>2</b>                            |
| Degree of protection provided against intrusion dust, accidental contact and water: | <b>IP20</b>                         |
|                                                                                     | <b>For indoor use</b>               |
| CE                                                                                  | <b>Declaration of conformity</b>    |