


Replaceability of light sources and/or control gears without product permanent damage



BASIC INFORMATION

|                |                       |
|----------------|-----------------------|
| Product name:  | TANGO LED C 6W NW     |
| Ideus index:   | 04251                 |
| EAN barcode:   | 5901477342516         |
| Colour:        | White                 |
| Materials:     | Polycarbonate PC, ABS |
| Height:        | 75 mm                 |
| Width:         | 172 mm                |
| Depth:         | 172 mm                |
| Box packaging: | 24 pcs                |

PRODUCT PARAMETERS

|                                                                                       |                                |
|---------------------------------------------------------------------------------------|--------------------------------|
| Power supply:                                                                         | 230V 50Hz                      |
| Power:                                                                                | 6 W                            |
| Dedicated light source:                                                               | N/A                            |
|                                                                                       | Non-replaceable light source   |
|                                                                                       | Do not use with a mains dimmer |
| Luminaire luminous flux:                                                              | 530 lm                         |
| Light source luminous flux:                                                           | 720 lm                         |
| Shelf life L70B50 in h:                                                               | 25 000 h                       |
| Product offer the possibility of adjusting the illumination direction:                | No                             |
| Degree of protection provided against intrusion, dust, accidental contact, and water: | IP65                           |
| Degree of protection against mechanical impacts:                                      | IK10                           |
| Light colour:                                                                         | Neutral white                  |
| Colour temperature:                                                                   | 4000 K                         |
| Luminous beam angle:                                                                  | 160°                           |
| Colour rendering index Ra:                                                            | 83                             |
|                                                                                       | For indoor or outdoor use      |
| Electric shock protection class:                                                      | 2                              |
| CE                                                                                    | Declaration of conformity      |