

PRODUCT INFORMATION SHEET





Replaceability of light sources and/or control gears without product permanent damage



BASIC INFORMATION

| Product name: | EDYTOR LED C MVS 15W NW |
|----------------|-------------------------|
| Ideus index: | 04335 |
| EAN barcode: | 5901477343353 |
| Colour: | White |
| Materials: | Polycarbonate PC |
| Height: | 50 mm |
| Width: | 265 mm |
| Depth: | 265 mm |
| Box packaging: | 10 pcs |
| | |

REMARKS

- microwave motion sensor included

- possibility of setting ambient lighting intensity (3-2000 lx) at which the device operates

- movement sensor operating angle 180°/360°
- motion detection range < 8 m
- lighting time regulation between 10 s and 12 min
- DIM function with run time from 0 s (OFF) to ∞
- operating frequency 5,8 GHz
- transmitter power 1,2 mW MAX

| PRODUCT PARAMETERS | | |
|---|--------------------------------|--|
| Power supply: | 230V 50Hz | |
| Power: | 15 W | |
| Dedicated light source: | N/A | |
| | Non-replaceable light source | |
| | Do not use with a mains dimmer | |
| Luminaire luminous flux: | 1 520 lm | |
| Light source luminous flux: | 2 030 lm | |
| Shelf life L70B50 in h: | 35 000 h | |
| Product offer the possibility of adjusting the illumination direction: | No | |
| Degree of protection provided against intrusion, dust, accidental contact, and water: | IP65 | |
| Degree of protection against mechanical impacts: | IK10 | |
| Light colour: | Neutral white | |
| Colour temperature: | 4000 K | |
| Luminous beam angle: | 160° | |
| Colour rendering index Ra: | 83 | |
| | For indoor or outdoor use | |
| Electric shock protection class: | 2 | |
| CE | Declaration of conformity | |
| | | |