


# PRODUCT INFORMATION SHEET



Replaceability of light sources and/or control gears without product permanent damage



## BASIC INFORMATION

|                |                         |
|----------------|-------------------------|
| Product name:  | <b>TABOR LED 18W NW</b> |
| Ideus index:   | <b>04752</b>            |
| EAN barcode:   | <b>5901477347528</b>    |
| Colour :       | <b>White</b>            |
| Materials:     | <b>Plastic</b>          |
| Height:        | <b>31 mm</b>            |
| Width:         | <b>600 mm</b>           |
| Depth:         | <b>51 mm</b>            |
| Box packaging: | <b>25 pcs</b>           |

## REMARKS

Serial connection up to 1000W possible

## PRODUCT PARAMETERS

|   |                                       |
|---|---------------------------------------|
| Power supply:   | <b>230V 50Hz</b>                      |
| Power:  | <b>18 W</b>                           |
| Dedicated light source:   | <b>SMD LED, in set</b>                |
|   | <b>Non-replaceable light source</b>   |
|   | <b>Do not use with a mains dimmer</b> |
| Luminaire luminous flux:  | <b>2 040 lm</b>                       |
| Light colour:   | <b>Neutral white</b>                  |
| Luminous beam angle:  | <b>160°</b>                           |
| Shelf life L70B50 in h:   | <b>35 000 h</b>                       |
| Product offer the possibility of adjusting the illumination direction:              | <b>No</b>                             |
| Light source luminous flux for a reference colour temperature:                      | <b>2 470 lm</b>                       |
| Colour temperature:   | <b>4000 K</b>                         |
| Colour rendering index Ra:  | <b>81</b>                             |
| Electric shock protection class:  | <b>2</b>                              |
| Degree of protection against mechanical impacts:                                    | <b>IK08</b>                           |
| Degree of protection provided against intrusion dust, accidental contact and water: | <b>IP65</b>                           |
|   | <b>For indoor or outdoor use</b>      |
| Displacement factor (DF, cos φ1):   | <b>0.723</b>                          |
| CE  | <b>Declaration of conformity</b>      |